



IPPM-4004H

**4 ch, (960H), H.264, High Performance ATM DVR
with HDMI, Built-in 7" LCD and 8 TB support**



FEATURES

- Up to 4 cameras with (1280x1024) display
- H.264 dual-stream video compression
- Full channel @ 960H realtime recording
- HDMI/VGA/TV simultaneous video output
- Built-in 7 inch screen
- Full channel synchronous realtime playback
- 3D intelligent positioning
- 8TB (4 SATA HDDs x 2TB each) + 1 eSATA External HDD port
- 3 x USB 2.0 ports
- Two way Audio with Speaker
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

SPECIFICATIONS

ATM DVR Model	IPPM-4004H
Features	
Operating System	Embedded LINUX
Input	4 channel, BNC
Output	1 x HDMI, 1 x VGA, 1 x TV, BNC
LCD	7" color LCD
Audio Input / Output	4 ch / 1 ch (Two way Audio with speaker)
Resolution	1280 x 1024 px
Display Split	1/4
Privacy Masking	4 x four-sided zones for privacy masking
OSD	Yes
Video/Audio Compression	H.264 / G.711
Resolution	960H (960x576 px/960x480 px)
Record Rate (Main Stream)	960H (1~25/30fps)
(Sub Stream)	CIF/QCIF(1~25/30fps)
Record Mode	Manual, Schedule, MD, Alarm), Stop
Video Detection	Motion Detection, Video Loss & Camera Blank
Alarm Input	9 channel
Relay Output	6 channel
Playback Channel	1/2/4
Backup Mode	USB Device / Network

ATM DVR Model	IPPM-4004H
Features (Continue)	
Ethernet	RJ-45 port (10/100M)
Network Functions	TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Internal HDD	8TB (4 SATA ports x 2TB each) + 1 x eSATA
USB	3 ports, USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
Environmental	
Working Temperature	-10°C ~ +55°C
Electrical	
Power Supply	AC 100 ~ 240 V, 50/60 Hz
Power Consumption	≤ 21W
Physical	
Dimensions (mm)	205 (W) x 305 (D) x 181 (H)
Weight	≤ 4.5 Kg (without HDD)
Regulatory Certifications	FCC, CE, C-TICK, UL

MADE IN KOREA