



IPPM-4004S

**4 ch, (960H), H.264, High Performance ATM DVR
with HDMI, Built-in 7" LCD and 4 TB support**



FEATURES

- Up to 4 cameras with (1280x1024) display
- H.264 dual-stream video compression
- Full channel @ 960H realtime recording
- HDMI/VGA/TV simultaneous video output
- Built-in 7 inch screen
- Full channel synchronous realtime playback
- 3D intelligent positioning
- 4TB (2 SATA HDDs x 2TB each)
- 2 x USB 2.0 ports
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

SPECIFICATIONS

NVR Model	IPPM-4004S
Features	
Operating System	Embedded LINUX
Input	4 channel, BNC
Output	1 x HDMI, 1 x VGA, 1 x TV, BNC
LCD	7" color LCD
Audio Input / Output	4 ch IN, BNC / 1 ch OUT, BNC
Resolution	1280 x 1024 px
Display Split	1/4
Privacy Masking	4 x four-sided zones for privacy masking
OSD	Yes
Video/Audio Compression	H.264 / G.711
Resolution	960H (960x576 px/960x480 px)
Record Rate (Main Stream)	960H (1~25/30fps)
(Sub Stream)	CIF/QCIF(1~25/30fps)
Record Mode	Manual, Schedule, MD, Alarm), Stop
Video Detection	Motion Detection, Video Loss & Camera Blank
Alarm Input	4 channel
Relay Output	2 channel
Playback Channel	1/2/4
Backup Mode	USB Device / Network

NVR Model	IPPM-4004S
Features (Continue)	
Ethernet	RJ-45 port (10/100M)
Network Functions	TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Internal HDD	4TB (2 SATA ports x 2TB each)
USB	2 ports, USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control

Environmental

Working Temperature -10°C ~ +55°C

Electrical

Power Supply AC 100 ~ 240 V, 50/60 Hz

Power Consumption ≤ 22W

Physical

Dimensions (mm) 205 (W) x 132 (D) x 325 (H)

Weight ≤ 4.5 Kg (without HDD)

Regulatory Certifications FCC, CE, C-TICK, UL

MADE IN KOREA